

Bottleless Dispenser

Features

Cabinet:

UV-protected high-density polyethylene (HDPE) cabinet. Eliminates the problem of rust and corrosion. Superior resistance to UV degradation. One piece mold is designed to allow cleaning and quick cabinet removal for convenient service. Handle on the back of the unit enables transport of the water cooler.

Faucets:

Durable polypropylene. Self-closing type. Easy to operate.

Drip Tray:

One piece ABS drip tray is easily removed for cleaning.

Cold Water Tank:

Hygienic stainless steel. External refrigerant evaporator. Mechanically wrapped around tank. Removable insulation in molded expanded bead polystyrene contaminant-resistant design. Adjustable cold water thermostat.

Dual Float Valve:

Water level is controlled with a Dual float valve. Dual float valve maintains water height in reservoir. Incoming water pressure range of 20-100psi.

Cold Water Thermostat:

Temperature is controlled to 35.6°F-53.6°F (2°C-12°C) by adjustable thermostat.

Refrigeration Unit:

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No lubricant needed. Refrigerant is controlled by accurately calibrated capillary tube. Quiet operation by the optimum design. Highly efficient cooling function.

Hot Water Tank:

Hygienic stainless steel. Highly efficient internal heating element. Non-adjustable thermostat with manual reset safety limiter. Convenient hot water ON/OFF switch. Fireproof insulation.

Hot Water Thermostat:

Water temperature is controlled to nearly 185°F (85°C) by automatic thermostat. Hot water ON/OFF switch is easily accessible in the control panel at the back of cabinet.

Electrical:

100V - 127V, 50/60Hz provided with power cord.

Quality:

The models covered by these specifications are manufactured to comply with the standards of overseas quality program.

Warranty:

One year on the sealed refrigeration system and most component parts.

Refrigerant Type:

R134a



Details

Manufacturer:

Clover

Model:

D7A

Dimensions:

12.4" Wide x 12.5" Deep x 39.3" High

Net Weight:

30 LBS.

Cold Water:

0.9 Gal of 50°F / Hr (3.5L of 10°C)

Hot Water:

2 Gal of 185°F / Hr (7.5L of 85°C)

Certified:

Energy Star Rated