

Cold/Room Temp Dispenser

Features

Cabinet:

UV-protected high-density polyethylene (HDPE) cabinet. Eliminates the problem of rust and corrosion. Superior resistance to UV degradation. One piece mold is designed to allow cleaning and quick cabinet removal for convenient service. Handle on the back of the unit enables transport of the water cooler.

Faucets:

Durable polypropylene. Self closing type. Easy to operate.

Drip Tray:

One piece ABS drip tray is easily removed for cleaning.

Cold Water Tank:

Hygienic stainless steel. External refrigerant evaporator. Mechanically wrapped around tank. Removable insulation in molded expanded bead polystyrene contaminant-resistant design. Adjustable cold water thermostat.

Cold Water Thermostat:

Temperature is controlled to 35.6°F-53.6°F (2°C-12°C) by adjustable thermostat.

Refrigeration Unit:

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No lubricant needed. Refrigerant is controlled by accurately calibrated capillary tube. Quiet operation by the optimum design. Highly efficient cooling function.

Electrical:

100V - 127V, 50/60Hz provided with power cord.

Quality:

The models covered by these specifications are manufactured to comply with the standards of overseas quality program.

Warranty:

One year on the sealed refrigeration system and most component parts.

Refrigerant Type:

R134a



Details

Manufacturer

Clover

Model

B7B

Dimensions

12.2" Wide x 12.2" Deep x 38.2" High

Net Weight

30 LBS.

Cold Water

0.9 Gal of 50°F / Hr (3.5L of 10°C)

Certified

Energy Star Rated