

Stainless Dispenser

Features

Cabinet:

Top and front panels are molded of ABS and side panels are of electric zinc coated steel with High Polymer Polyester resin.

Faucets:

Durable polypropylene. Self closing type. Easy to operate.

Drip Tray:

One piece ABS drip tray is easily removed for cleaning.

Cold Water Tank:

Hygienic stainless steel. External refrigerant evaporator. Mechanically wrapped around tank. Removable insulation in molded expanded bead polystyrene contaminant-resistant design. Adjustable cold water thermostat.

Cold Water Thermostat:

Temperature is controlled to 35.6°F-53.6°F (2°C-12°C) by adjustable thermostat.

Refrigeration Unit:

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No lubricant needed. Refrigerant is controlled by accurately calibrated capillary tube. Quiet operation by the optimum design. Highly efficient cooling function.

Hot Water Tank:

Hygienic stainless steel. Highly efficient internal heating element. Non-adjustable thermostat with manual reset safety limiter. Convenient hot water ON/OFF switch. Fireproof insulation.

Hot Water Thermostat:

Water temperature is controlled to nearly 185°F (85°C) by automatic thermostat. Hot water ON/OFF switch is easily accessible in the control panel at the back of cabinet.

Electrical:

100V - 127V, 50/60Hz provided with power cord.

Quality:

The models covered by these specifications are manufactured to comply with the standards of overseas quality program.

Warranty:

One year on the sealed refrigeration system and most component parts.

Refrigerant Type:

R134a

Details

Manufacturer

Clover

Model

B14A

Dimensions

12.3" Wide x 12.7" Deep x 37.9" High

Net Weight

32 LBS.

Cold Water

0.9 Gal of 50°F / Hr (3.5L of 10°C)

Hot Water

2 Gal of 185°F / Hr (7.5L of 85°C)

Certified

Energy Star Rated

